


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0090	UPDATED TO NEW STANDARD. REMOVED DIM .50. REMOVED DIM ϕ .129-.125 THRU ALL. -1 ADDED DIM ϕ .125-.129 (P.F. -7). .375+.000/-0.05. CH'D DIM WAS ϕ .752/.750 \pm .90 IS ϕ .752/.750 \pm .90 (S.F. -3). WAS 3X ϕ .3756/.3750 \pm .50 IS 3X ϕ .3756/.3750 \pm .50 (P.F. -5). -3 ADDED DIMS ϕ .125-.129 THRU ALL. .375+.005/-0.00; CH'D DIM WS ϕ .7475/.7463 IS ϕ .7475/.7463 (S.F. -1); CH'D COURSE KNURL TO MEDIUM KNURL. -5 CH'D DIM WAS .050 X 45° IS .05 X 45°; WAS ϕ .3764/.3760 (P.F. -5).	8/4/2016	DEW	SM






NOTE:
REF. EUROCOPTER T/N: 332A93-3690-00.

DART AEROSPACE	
TITLE CHIP DETECTOR HAFTING TOOL	
DWG NO. RBE332A93-3690-00	REV 2
MAT'L REAT TREAT FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX \pm .005 FRACTIONS \pm 1/8 .XX \pm .01 ANGLES \pm 5° .X \pm .1 SURFACES = 125°
SPEC	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
DRAWN BY: MARPET	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
CHECKED: DUERFELDT	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
OPPS APPR: ANDERSON	USED ON MODEL
QA APPR: LINDSAY	AS332
APPROVED: MACKOVJAK	
SCALE 1:4	DATE 6/3/2013
SHEET 1 OF 4	

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	BODY	6061		2
			-3	1	HANDLE	6061		3
			-5	3	PIN	6061		4
		B/O	-7	1	SPRING PIN	STEEL	1/8 X 7/8 (MCMASTER-CARR # 90692A699)	1

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0090	-1 ADDED DIM $\varnothing .125-.129$ (P.F. -7). $.375^{+.000}/_{-.005}$ CH'D DIM WAS $\varnothing .752/.750 \nabla .90$ IS $\varnothing .752/.750 \nabla .90$ (S.F. -3), WAS 3X $\varnothing .3756/.3750 \nabla .50$ IS 3X $\varnothing .3756/.3750 \nabla .50$ (P.F. -5).	8/4/2016	DEW	SM





HIDDEN LINES OMITTED FOR CLARITY.

(-1)
BODY

DART AEROSPACE	
TITLE CHIP DETECTOR HAFTING TOOL	
DWG NO. RBE332A93-3690-00-1	REV 2
MAT'L 6061	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX $\pm .005$ FRACTIONS $\pm 1/8$
FINISH CLEAR ANODIZE	.XX $\pm .01$ ANGLES $\pm 5^\circ$
SPEC MIL-A-8625F, TYPE II, CLASS I	.X $\pm .1$ SURFACES = 125 ✓
DRAWN BY: MARPET	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: MACKOVJAK	AS332
SCALE 1:2	DATE 6/3/2013
SHEET 2 OF 4	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0090	-3 ADDED DIMS $\varnothing .125-.129$ THRU ALL, $.375+ .005/- .000$; CH'D DIM WS $\varnothing .7475/.7463$ IS $\varnothing .7475/.7463$ (S.F. -1); CH'D COURSE KNURL TO MEDIUM KNURL.	8/4/2016	DEW	SM





(3)

HANDLE

DART AEROSPACE	
TITLE CHIP DETECTOR HAFTING TOOL	
DWG NO. RBE332A93-3690-00-3	REV 2
MAT'L 6061	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX $\pm .005$ FRACTIONS $\pm 1/8$
FINISH CLEAR ANODIZE	.XX $\pm .01$ ANGLES $\pm 5^\circ$
SPEC MIL-A-8625F, TYPE II, CLASS I	.X $\pm .1$ SURFACES = 125
DRAWN BY: MARPET	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: MACKOVJAK	AS332
SCALE 1:2	DATE 6/3/2013
SHEET 3 OF 4	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	16-0090	-5 CH'D DIM WAS .050 X 45° IS .05 X 45°; WAS Ø.3764/.3760 (P.F. -5).	8/4/2016	DEW	SM



(-5)
PIN

DART AEROSPACE	
TITLE CHIP DETECTOR HAFTING TOOL	
DWG NO. RBE332A93-3690-00-5	REV 2
MAT'L 6061	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH CLEAR ANODIZE	.XXX ± .005 FRACTIONS ± 1/8
SPEC MIL-A-8625F, TYPE II, CLASS I	.XX ± .01 ANGLES ± .5°
DRAWN BY: MARPET	.X ± .1 SURFACES = 125/
CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: MACKOVJAK	AFTER PLATING
SCALE 2:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 6/3/2013	USED ON MODEL
SHEET 4 OF 4	AS332